

# **888 Item Maintenance**

**X12/V4030/888: 888 Item Maintenance**

**Author: DOT FOODS, INC.**  
**Publication: July 14, 2005**

# 888 Item Maintenance

Functional Group=QG

This Draft Standard for Trial Use provides the format and establishes the data contents of the Item Maintenance Transaction Set (888) for use within the context of an Electronic Data Interchange (EDI) environment. This transaction set is used to enable a manufacturer, supplier, broker, or agent to provide detailed finished goods product information to a partner in a consumer goods market. This transaction set can be used to provide information about new products or changes in existing product specifications. Price changes will not be sent with this transaction set, but can be sent with the Price Change Transaction Set (879).

## Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

## Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	ST	Transaction Set Header	M	1			Must use

### LOOP ID - 0100

					<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
					≥1	N1/0200L	
0200	N1	Name	M	1		N1/0200	Must use
0400	N3	Address Information	O	2			Used
0500	N4	Geographic Location	O	1			Used

### LOOP ID - 0100

					<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
					≥1	N1/0200L	
0200	N1	Name	M	1		N1/0200	Must use
0400	N3	Address Information	O	2			Used
0500	N4	Geographic Location	O	1			Used
0700	G61	Contact	O	>1			Used
0700	G61	Contact	O	>1			Used
0860	G62	Date/Time	M	1			Must use

## Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
------------	-----------	---------------------	------------	----------------	---------------	--------------	--------------

### LOOP ID - 0300

					<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
					≥1		
0100	G53	Maintenance Type	M	1			Must use
0300	NTE	Note/Special Instruction	O	20			Used

### LOOP ID - 0310

					<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
					≥1		
0350	LX	Assigned Number	M	1			Must use
0400	G39	Item Characteristics - Vendor's Selling Unit	O	1			Used
0500	G69	Line Item Detail - Description	O	5			Used
0500	G69	Line Item Detail - Description	O	5			Used
0500	G69	Line Item Detail - Description	O	5			Used
0500	G69	Line Item Detail - Description	O	5			Used
0560	LIN	Item Identification	O	1			Used
0600	G23	Terms of Sale	O	10			Used
0900	G26	Pricing Conditions	O	2			Used
1510	N9	Reference Identification	O	10			Used

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
1510	N9	Reference Identification	O	10			Used
1510	N9	Reference Identification	O	10			Used
1520	UIT	Unit Detail	M	10			Used
1530	MEA	Measurements	O	10			Used
<b>LOOP ID - 0311</b>					<b>≥1</b>		
1600	PAL	Pallet Information	O	>1			Used
<b>LOOP ID - 0312</b>					<b>≥1</b>		
1650	G55	Item Characteristics - Consumer Unit	O	1			Used
1775	REF	Reference Identification	O	10			Used
2000	SE	Transaction Set Trailer	M	1			Must use

### Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

### Notes:

- 1/0200L One iteration of the N1 loop should be used to identify the buying party (BY) to establish the area or location for which the item maintenance applies.
- 1/0200 One iteration of the N1 loop should be used to identify the buying party (BY) to establish the area or location for which the item maintenance applies.
- 1/0200L One iteration of the N1 loop should be used to identify the buying party (BY) to establish the area or location for which the item maintenance applies.
- 1/0200 One iteration of the N1 loop should be used to identify the buying party (BY) to establish the area or location for which the item maintenance applies.

# ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

To start and identify an interchange of zero or more functional groups and interchange-related control segments

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	<b>Authorization Information Qualifier</b>	M	ID	2/2	Must use
		<b>Description:</b> Code identifying the type of information in the Authorization Information				
		<b>Code Name</b>				
		00 No Authorization Information Present (No Meaningful Information in I02)				
ISA02	I02	<b>Authorization Information</b>	M	AN	10/10	Must use
		<b>Description:</b> Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)				
ISA03	I03	<b>Security Information Qualifier</b>	M	ID	2/2	Must use
		<b>Description:</b> Code identifying the type of information in the Security Information				
		<b>Code Name</b>				
		00 No Security Information Present (No Meaningful Information in I04)				
ISA04	I04	<b>Security Information</b>	M	AN	10/10	Must use
		<b>Description:</b> This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)				
ISA05	I05	<b>Interchange ID Qualifier</b>	M	ID	2/2	Must use
		<b>Description:</b> Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified				
		<b>Code Name</b>				
		08 UCC EDI Communications ID (Comm ID)				
ISA06	I06	<b>Interchange Sender ID</b>	M	AN	15/15	Must use
		<b>Description:</b> Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element				
		<b>Dot Foods: 9288030000</b>				
ISA07	I05	<b>Interchange ID Qualifier</b>	M	ID	2/2	Must use
		<b>Description:</b> Code indicating the system/method of				

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		code structure used to designate the sender or receiver ID element being qualified <b>All valid standard codes are used.</b>				
ISA08	I07	<b>Interchange Receiver ID</b>	M	AN	15/15	Must use
		<b>Description:</b> Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them				
ISA09	I08	<b>Interchange Date</b>	M	DT	6/6	Must use
		<b>Description:</b> Date of the interchange				
ISA10	I09	<b>Interchange Time</b>	M	TM	4/4	Must use
		<b>Description:</b> Time of the interchange				
ISA11	I65	<b>Repetition Separator</b>	M		1/1	Must use
		<b>Description:</b> Type is not applicable; the repetition separator is a delimiter and not a data element; this field provides the delimiter used to separate repeated occurrences of a simple data element or a composite data structure; this value must be different than the data element separator, component element separator, and the segment terminator				
ISA12	I11	<b>Interchange Control Version Number</b>	M	ID	5/5	Must use
		<b>Description:</b> Code specifying the version number of the interchange control segments				
		<b>Code Name</b> 00403 Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1999				
ISA13	I12	<b>Interchange Control Number</b>	M	N0	9/9	Must use
		<b>Description:</b> A control number assigned by the interchange sender				
ISA14	I13	<b>Acknowledgment Requested</b>	M	ID	1/1	Must use
		<b>Description:</b> Code indicating sender's request for an interchange acknowledgment				
		<b>Code Name</b> 0 No Acknowledgment Requested				
ISA15	I14	<b>Usage Indicator</b>	M	ID	1/1	Must use
		<b>Description:</b> Code indicating whether data enclosed by this interchange envelope is test, production or information				
		<b>Code Name</b> P Production Data				
ISA16	I15	<b>Component Element Separator</b>	M		1/1	Must use

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		<b>Description:</b> Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator				

# GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

To indicate the beginning of a functional group and to provide control information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	<b>Functional Identifier Code</b>	M	ID	2/2	Must use
		<b>Description:</b> Code identifying a group of application related transaction sets				
		<b>Code Name</b>				
		QG Product Information (878, 879, 888, 889, 896)				
GS02	142	<b>Application Sender's Code</b>	M	AN	2/15	Must use
		<b>Description:</b> Code identifying party sending transmission; codes agreed to by trading partners				
		<b>Dot Foods: 9288030000</b>				
GS03	124	<b>Application Receiver's Code</b>	M	AN	2/15	Must use
		<b>Description:</b> Code identifying party receiving transmission; codes agreed to by trading partners				
GS04	373	<b>Date</b>	M	DT	8/8	Must use
		<b>Description:</b> Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year				
GS05	337	<b>Time</b>	M	TM	4/8	Must use
		<b>Description:</b> Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)				
GS06	28	<b>Group Control Number</b>	M	N0	1/9	Must use
		<b>Description:</b> Assigned number originated and maintained by the sender				
GS07	455	<b>Responsible Agency Code</b>	M	ID	1/2	Must use
		<b>Description:</b> Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480				
		<b>Code Name</b>				
		X Accredited Standards Committee X12				
GS08	480	<b>Version / Release / Industry Identifier Code</b>	M	AN	1/12	Must use

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		<p><b>Description:</b> Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed</p> <p><b>Code    Name</b></p> <p>004030 Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1999</p>				

**Semantics:**

1. GS04 is the group date.
2. GS05 is the group time.
3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

**Comments:**

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

# ST Transaction Set Header

Pos: 0100	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

To indicate the start of a transaction set and to assign a control number

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	<b>Transaction Set Identifier Code</b>	M	ID	3/3	Must use
		<b>Description:</b> Code uniquely identifying a Transaction Set				
		<b>Code Name</b>				
		888 Item Maintenance				
ST02	329	<b>Transaction Set Control Number</b>	M	AN	4/9	Must use
		<b>Description:</b> Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

## Semantics:

1. The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
2. The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation convention to match the transaction set definition.

# N1 Name

Pos: 0200	Max: 1
Heading - Mandatory	
Loop: 0100	Elements: 4

User Option (Usage): Must use

To identify a party by type of organization, name, and code

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	<b>Entity Identifier Code</b>  <b>Description:</b> Code identifying an organizational entity, a physical location, property or an individual  <b>Code Name</b> BY Buying Party (Purchaser)	M	ID	2/3	Must use
N102	93	<b>Name</b>  <b>Description:</b> Free-form name	X	AN	1/60	Used
N103	66	<b>Identification Code Qualifier</b>  <b>Description:</b> Code designating the system/method of code structure used for Identification Code (67)  <b>Code Name</b> 9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix	X	ID	1/2	Used
N104	67	<b>Identification Code</b>  <b>Description:</b> Code identifying a party or other code	X	AN	2/80	Used

## Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

## Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

# N3 Address Information

Pos: 0400	Max: 2
Heading - Optional	
Loop: 0100	Elements: 2

User Option (Usage): Used

To specify the location of the named party

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	<b>Address Information</b>	M	AN	1/55	Must use
		<b>Description:</b> Address information				
N302	166	<b>Address Information</b>	O	AN	1/55	Used
		<b>Description:</b> Address information				

# N4 Geographic Location

Pos: 0500	Max: 1
Heading - Optional	
Loop: 0100	Elements: 3

User Option (Usage): Used

To specify the geographic place of the named party

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	<b>City Name</b>	O	AN	2/30	Used
		<b>Description:</b> Free-form text for city name				
N402	156	<b>State or Province Code</b>	X	ID	2/2	Used
		<b>Description:</b> Code (Standard State/Province) as defined by appropriate government agency				
N403	116	<b>Postal Code</b>	O	ID	3/15	Used
		<b>Description:</b> Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				

## Syntax Rules:

1. E0207 - Only one of N402 or N407 may be present.
2. C0605 - If N406 is present, then N405 is required.
3. C0704 - If N407 is present, then N404 is required.

## Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

# N1 Name

Pos: 0200	Max: 1
Heading - Mandatory	
Loop: 0100	Elements: 4

User Option (Usage): Must use

To identify a party by type of organization, name, and code

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	<b>Entity Identifier Code</b>	M	ID	2/3	Must use
		<b>Description:</b> Code identifying an organizational entity, a physical location, property or an individual				
		<b>Code Name</b>				
		VN Vendor				
N102	93	<b>Name</b>	X	AN	1/60	Used
		<b>Description:</b> Free-form name				
N103	66	<b>Identification Code Qualifier</b>	X	ID	1/2	Used
		<b>Description:</b> Code designating the system/method of code structure used for Identification Code (67)				
		<b>Code Name</b>				
		9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix				
N104	67	<b>Identification Code</b>	X	AN	2/80	Used
		<b>Description:</b> Code identifying a party or other code				

## Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

## Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

# N3 Address Information

Pos: 0400	Max: 2
Heading - Optional	
Loop: 0100	Elements: 2

User Option (Usage): Used

To specify the location of the named party

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	<b>Address Information</b>	M	AN	1/55	Must use
		<b>Description:</b> Address information				
N302	166	<b>Address Information</b>	O	AN	1/55	Used
		<b>Description:</b> Address information				

# N4 Geographic Location

Pos: 0500	Max: 1
Heading - Optional	
Loop: 0100	Elements: 3

User Option (Usage): Used

To specify the geographic place of the named party

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	<b>City Name</b>	O	AN	2/30	Used
		<b>Description:</b> Free-form text for city name				
N402	156	<b>State or Province Code</b>	X	ID	2/2	Used
		<b>Description:</b> Code (Standard State/Province) as defined by appropriate government agency				
N403	116	<b>Postal Code</b>	O	ID	3/15	Used
		<b>Description:</b> Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				

## Syntax Rules:

1. E0207 - Only one of N402 or N407 may be present.
2. C0605 - If N406 is present, then N405 is required.
3. C0704 - If N407 is present, then N404 is required.

## Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

# G61 Contact

Pos: 0700	Max: >1
Heading - Optional	
Loop: N/A	Elements: 4

User Option (Usage): Used

To identify a person or office to whom communications should be directed

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G6101	366	<b>Contact Function Code</b>  <b>Description:</b> Code identifying the major duty or responsibility of the person or group named  <b>Code Name</b> AM Administrator	M	ID	2/2	Must use
G6102	93	<b>Name</b>  <b>Description:</b> Free-form name	M	AN	1/60	Must use
G6103	365	<b>Communication Number Qualifier</b>  <b>Description:</b> Code identifying the type of communication number  <b>Code Name</b> TE Telephone	X	ID	2/2	Used
G6104	364	<b>Communication Number</b>  <b>Description:</b> Complete communications number including country or area code when applicable	X	AN	1/256	Used

## Syntax Rules:

1. P0304 - If either G6103 or G6104 is present, then the other is required.

## Comments:

1. G6103 qualifies G6104.

# G61 Contact

Pos: 0700	Max: >1
Heading - Optional	
Loop: N/A	Elements: 4

User Option (Usage): Used

To identify a person or office to whom communications should be directed

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G6101	366	<b>Contact Function Code</b>  <b>Description:</b> Code identifying the major duty or responsibility of the person or group named  <b>Code Name</b> BD Buyer Name or Department	M	ID	2/2	Must use
G6102	93	<b>Name</b>  <b>Description:</b> Free-form name	M	AN	1/60	Must use
G6103	365	<b>Communication Number Qualifier</b>  <b>Description:</b> Code identifying the type of communication number  <b>Code Name</b> TE Telephone	X	ID	2/2	Used
G6104	364	<b>Communication Number</b>  <b>Description:</b> Complete communications number including country or area code when applicable	X	AN	1/256	Used

## Syntax Rules:

1. P0304 - If either G6103 or G6104 is present, then the other is required.

## Comments:

1. G6103 qualifies G6104.

# G62 Date/Time

Pos: 0860	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

To specify pertinent dates and times

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G6201	432	<b>Date Qualifier</b> <b>Description:</b> Code specifying type of date <b>Code Name</b> 09 Process Date	X	ID	2/2	Used
G6202	373	<b>Date</b> <b>Description:</b> Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year	X	DT	8/8	Used
G6203	176	<b>Time Qualifier</b> <b>Description:</b> Code specifying the reported time <b>Code Name</b> W Effective Time	X	ID	1/2	Used
G6204	337	<b>Time</b> <b>Description:</b> Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	X	TM	4/8	Used

## Syntax Rules:

1. R0103 - At least one of G6201 or G6203 is required.
2. P0102 - If either G6201 or G6202 is present, then the other is required.
3. P0304 - If either G6203 or G6204 is present, then the other is required.

# G53 Maintenance Type

Pos: 0100	Max: 1
Detail - Mandatory	
Loop: 0300	Elements: 1

User Option (Usage): Must use

To identify the specific type of item maintenance

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G5301	875	Maintenance Type Code	M	ID	3/3	Must use

**Description:** Code identifying the specific type of item maintenance

**Code Name**

- 001 Change
- 002 Delete
- 003 Add Full Item Detail
- 004 Withdraw Item (Temporary)
- 005 Restore Item

# NTE Note/Special Instruction

Pos: 0300	Max: 20
Detail - Optional	
Loop: 0300	Elements: 1

User Option (Usage): Used

To transmit information in a free-form format, if necessary, for comment or special instruction

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
NTE02	352	Description	M	AN	1/80	Must use

**Description:** A free-form description to clarify the related data elements and their content

## Comments:

1. The NTE segment permits free-form information/data which, under ANSI X12 standard implementations, is not machine processible. The use of the NTE segment should therefore be avoided, if at all possible, in an automated environment.

# LX Assigned Number

Pos: 0350	Max: 1
Detail - Mandatory	
Loop: 0310	Elements: 1

User Option (Usage): Must use

To reference a line number in a transaction set

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LX01	554	Assigned Number	M	N0	1/6	Must use

**Description:** Number assigned for differentiation within a transaction set

# G39 Item Characteristics - Vendor's Selling Unit

Pos: 0400	Max: 1
Detail - Optional	
Loop: 0310	Elements: 23

User Option (Usage): Used

To identify a vendor's selling unit or to provide physical characteristics relative to a vendor's selling unit

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G3901	438	<b>U.P.C. Case Code</b>  <b>Description:</b> Code (Universal Product Code - U.P.C.) including two high order digits identifying the "system" (U.S. Grocery = 00, 06 or 07; U.S. Drug = 03); using the U.S. Grocery system, the next ten digits are: Manufacturer (5) Case Code (5)	X	AN	12/12	Used
G3902	235	<b>Product/Service ID Qualifier</b>  <b>Description:</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)  <b>Code Name</b> UK EAN/UCC - 14	X	ID	2/2	Used
G3903	234	<b>Product/Service ID</b>  <b>Description:</b> Identifying number for a product or service	X	AN	1/48	Used
G3904	152	<b>Special Handling Code</b>  <b>Description:</b> Code specifying special transportation handling instructions  <b>Code Name</b> DNF Do Not Freeze FRZ Accepted by Carrier at Owner's Risk of Freezing MRF Refrigerated	O	ID	2/3	Used
G3905	395	<b>Unit Weight</b>  <b>Description:</b> Numeric value of weight per unit	X	R	1/8	Used
G3906	187	<b>Weight Qualifier</b>  <b>Description:</b> Code defining the type of weight  <b>Code Name</b> G Gross Weight	X	ID	1/2	Used
G3907	188	<b>Weight Unit Code</b>  <b>Description:</b> Code specifying the weight unit  <b>Code Name</b> L Pounds	X	ID	1/1	Used

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G3908	65	<b>Height</b>  <b>Description:</b> Vertical dimension of an object measured when the object is in the upright position	X	R	1/8	Used
G3909	355	<b>Unit or Basis for Measurement Code</b>  <b>Description:</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken  <u>Code Name</u> IN Inch	X	ID	2/2	Used
G3910	189	<b>Width</b>  <b>Description:</b> Shorter measurement of the two horizontal dimensions measured with the object in the upright position	X	R	1/8	Used
G3911	355	<b>Unit or Basis for Measurement Code</b>  <b>Description:</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken  <u>Code Name</u> IN Inch	X	ID	2/2	Used
G3912	82	<b>Length</b>  <b>Description:</b> Largest horizontal dimension of an object measured when the object is in the upright position	X	R	1/8	Used
G3913	355	<b>Unit or Basis for Measurement Code</b>  <b>Description:</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken  <u>Code Name</u> IN Inch	X	ID	2/2	Used
G3914	183	<b>Volume</b>  <b>Description:</b> Value of volumetric measure	X	R	1/8	Used
G3915	355	<b>Unit or Basis for Measurement Code</b>  <b>Description:</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken  <u>Code Name</u> CF Cubic Feet	X	ID	2/2	Used
G3916	416	<b>Pallet Block and Tiers</b>  <b>Description:</b> Code indicating pallet and load structure; first three digits indicate the number of cases per layer, last three digits indicate the number of layers per pallet	O	N0	6/6	Used

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G3917	356	<b>Pack</b> <b>Description:</b> The number of inner containers, or number of eaches if there are no inner containers, per outer container	O	N0	1/6	Used
G3918	357	<b>Size</b> <b>Description:</b> Size of supplier units in pack	X	R	1/8	Used
G3919	355	<b>Unit or Basis for Measurement Code</b> <b>Description:</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	X	ID	2/2	Used
		<b><u>Code</u> <u>Name</u></b>				
		12 Packet				
		1N Count				
		BA Bale				
		BD Bundle				
		BK Book				
		CN Can				
		CU Cup				
		DI Dispenser				
		DZ Dozen				
		EA Each				
		GA Gallon				
		GR Gram				
		LB Pound				
		LT Liter				
		ML Milliliter				
		OZ Ounce - Av				
		PR Pair				
		QT Quart				
		RL Roll				
		ST Set				
		V2 Pouch				
G3923	235	<b>Product/Service ID Qualifier</b> <b>Description:</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID	2/2	Used
		<b><u>Code</u> <u>Name</u></b>				
		VN Vendor's (Seller's) Item Number				
G3924	234	<b>Product/Service ID</b> <b>Description:</b> Identifying number for a product or service	X	AN	1/48	Used
		<b>Dot Foods: <i>Dot item number</i></b>				
G3925	187	<b>Weight Qualifier</b> <b>Description:</b> Code defining the type of weight	X	ID	1/2	Used

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		<u>Code</u> <u>Name</u>				
		N Actual Net Weight				
G3926	395	<b>Unit Weight</b>	X	R	1/8	Used
		<b>Description:</b> Numeric value of weight per unit				

### Syntax Rules:

1. R0102 - At least one of G3901 or G3902 is required.
2. P0203 - If either G3902 or G3903 is present, then the other is required.
3. P050607 - If either G3905, G3906 or G3907 are present, then the others are required.
4. P0607 - If either G3906 or G3907 is present, then the other is required.
5. P0809 - If either G3908 or G3909 is present, then the other is required.
6. P1011 - If either G3910 or G3911 is present, then the other is required.
7. P1213 - If either G3912 or G3913 is present, then the other is required.
8. P1415 - If either G3914 or G3915 is present, then the other is required.
9. P1819 - If either G3918 or G3919 is present, then the other is required.
10. P2324 - If either G3923 or G3924 is present, then the other is required.
11. P2526 - If either G3925 or G3926 is present, then the other is required.

# G69 Line Item Detail - Description

Pos: 0500	Max: 5
Detail - Optional	
Loop: 0310	Elements: 1

User Option (Usage): Used

To describe an item in free-form format

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G6901	369	Free-form Description	M	AN	1/45	Must use

**Description:** Free-form descriptive text

## Dot Foods:

*Abbreviated item description*

# G69 Line Item Detail - Description

Pos: 0500	Max: 5
Detail - Optional	
Loop: 0310	Elements: 1

User Option (Usage): Used

To describe an item in free-form format

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G6901	369	<b>Free-form Description</b>	M	AN	1/45	Must use

**Description:** Free-form descriptive text

## Dot Foods:

*Full item description - Characters 1 - 45*

# G69 Line Item Detail - Description

Pos: 0500	Max: 5
Detail - Optional	
Loop: 0310	Elements: 1

User Option (Usage): Used

To describe an item in free-form format

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G6901	369	Free-form Description	M	AN	1/45	Must use

**Description:** Free-form descriptive text

## Dot Foods:

*Full item description - Characters 46 - 90*

# G69 Line Item Detail - Description

Pos: 0500	Max: 5
Detail - Optional	
Loop: 0310	Elements: 1

User Option (Usage): Used

To describe an item in free-form format

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G6901	369	Free-form Description	M	AN	1/45	Must use

**Description:** Free-form descriptive text

## Dot Foods:

*Full item description - Characters 91 - 100*

# LIN Item Identification

Pos: 0560	Max: 1
Detail - Optional	
Loop: 0310	Elements: 6

User Option (Usage): Used

To specify basic item identification data

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN02	235	<b>Product/Service ID Qualifier</b>	M	ID	2/2	Must use
		<b>Description:</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		<b>Code Name</b>				
		MG Manufacturer's Part Number				
LIN03	234	<b>Product/Service ID</b>	M	AN	1/48	Must use
		<b>Description:</b> Identifying number for a product or service				
LIN04	235	<b>Product/Service ID Qualifier</b>	X	ID	2/2	Used
		<b>Description:</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		<b>Code Name</b>				
		PI Purchaser's Item Code				
LIN05	234	<b>Product/Service ID</b>	X	AN	1/48	Used
		<b>Description:</b> Identifying number for a product or service				
LIN06	235	<b>Product/Service ID Qualifier</b>	X	ID	2/2	Used
		<b>Description:</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		<b>Code Name</b>				
		BL Brand/Label				
LIN07	234	<b>Product/Service ID</b>	X	AN	1/48	Used
		<b>Description:</b> Identifying number for a product or service				

## Syntax Rules:

1. P0405 - If either LIN04 or LIN05 is present, then the other is required.
2. P0607 - If either LIN06 or LIN07 is present, then the other is required.
3. P0809 - If either LIN08 or LIN09 is present, then the other is required.
4. P1011 - If either LIN10 or LIN11 is present, then the other is required.
5. P1213 - If either LIN12 or LIN13 is present, then the other is required.

6. P1415 - If either LIN14 or LIN15 is present, then the other is required.
7. P1617 - If either LIN16 or LIN17 is present, then the other is required.
8. P1819 - If either LIN18 or LIN19 is present, then the other is required.
9. P2021 - If either LIN20 or LIN21 is present, then the other is required.
10. P2223 - If either LIN22 or LIN23 is present, then the other is required.
11. P2425 - If either LIN24 or LIN25 is present, then the other is required.
12. P2627 - If either LIN26 or LIN27 is present, then the other is required.
13. P2829 - If either LIN28 or LIN29 is present, then the other is required.
14. P3031 - If either LIN30 or LIN31 is present, then the other is required.

**Semantics:**

1. LIN01 is the line item identification

**Comments:**

1. See the Data Dictionary for a complete list of IDs.
2. LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

# G23 Terms of Sale

Pos: 0600	Max: 10
Detail - Optional	
Loop: 0310	Elements: 5

User Option (Usage): Used

To specify the terms of sale

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G2301	336	<b>Terms Type Code</b>	M	ID	2/2	Must use
		<b>Description:</b> Code identifying type of payment terms				
		<b>Code Name</b>				
		01 Basic				
		05 Discount Not Applicable				
G2302	333	<b>Terms Basis Date Code</b>	M	ID	1/2	Must use
		<b>Description:</b> Code identifying the beginning of the terms period				
		<b>Code Name</b>				
		3 Invoice Date				
G2305	338	<b>Terms Discount Percent</b>	O	R	1/6	Used
		<b>Description:</b> Terms discount percentage, expressed as a percent, available to the purchaser if an invoice is paid on or before the Terms Discount Due Date				
G2307	351	<b>Terms Discount Days Due</b>	O	N0	1/3	Used
		<b>Description:</b> Number of days in the terms discount period by which payment is due if terms discount is earned				
G2309	386	<b>Terms Net Days</b>	X	N0	1/3	Used
		<b>Description:</b> Number of days until total invoice amount is due (discount not applicable)				

## Syntax Rules:

1. R0809 - At least one of G2308 or G2309 is required.

## Comments:

1. The G23 segment may be used for the detail or the total transaction set level. Refer to the transaction set assumptions for details on proper usage.
2. If G2301 equals "04" (deferred or installment) then either G2313 or G2314 is required and the data in the segment pertains only to the portion of the invoice described in G2313 or G2314. If G2301 equals "11" (elective) then G2304 is required. If G2301 is not equal to "05" (discount not applicable) then (G2305 or G2310) and (G2306 or G2307) is required. If G2301 equals "ZZ" (other) then G2315 is required. Multiple use of this segment when G2301 equals "04" (deferred or installment) always implies an "AND" relationship. When G2301 equals "06" (mixed) or "11" (elective) an "OR" relationship is always implied.

3. G2310 is a memo figure requiring specific payment performance and therefore should not be negative.
4. When elective terms are offered in a deferred or installment situation, G2316 (Installment Group Indicator - DE 713) must be used to properly group the terms within each installment.

# G26 Pricing Conditions

Pos: 0900	Max: 2
Detail - Optional	
Loop: 0310	Elements: 1

User Option (Usage): Used

To specify vendor's conditions related to price change

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G2601	290	Price Condition Code	M	ID	2/2	Must use

**Description:** Code identifying a particular condition applicable to a price change

**Code Name**

15 Order Lead Time Requirement

## Syntax Rules:

1. P0203 - If either G2602 or G2603 is present, then the other is required.
2. P040506 - If either G2604, G2605 or G2606 are present, then the others are required.

## Dot Foods:

*This segment will only appear if the item is a non-stock item.*

# N9 Reference Identification

Pos: 1510	Max: 10
Detail - Optional	
Loop: 0310	Elements: 3

User Option (Usage): Used

To transmit identifying information as specified by the Reference Identification Qualifier

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	<b>Reference Identification Qualifier</b>	M	ID	2/3	Must use
		<b>Description:</b> Code qualifying the Reference Identification				
		<b>Code Name</b>				
		4P Affiliation Number				
N902	127	<b>Reference Identification</b>	X	AN	1/50	Used
		<b>Description:</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier				
		<b>Dot Foods: <i>Buying Group Number</i></b>				
N903	369	<b>Free-form Description</b>	X	AN	1/45	Used
		<b>Description:</b> Free-form descriptive text				
		<b>Dot Foods: <i>Buying Group Name</i></b>				

## Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

## Semantics:

1. N906 reflects the time zone which the time reflects.
2. N907 contains data relating to the value cited in N902.

# N9 Reference Identification

Pos: 1510	Max: 10
Detail - Optional	
Loop: 0310	Elements: 3

User Option (Usage): Used

To transmit identifying information as specified by the Reference Identification Qualifier

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	<b>Reference Identification Qualifier</b>	M	ID	2/3	Must use
		<b>Description:</b> Code qualifying the Reference Identification				
		<b>Code Name</b>				
		PG Product Group				
N902	127	<b>Reference Identification</b>	X	AN	1/50	Used
		<b>Description:</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier				
		<b>Dot Foods: IFDA Category Number</b>				
N903	369	<b>Free-form Description</b>	X	AN	1/45	Used
		<b>Description:</b> Free-form descriptive text				
		<b>Dot Foods: IFDA Category Description</b>				

## Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

## Semantics:

1. N906 reflects the time zone which the time reflects.
2. N907 contains data relating to the value cited in N902.

# N9 Reference Identification

Pos: 1510	Max: 10
Detail - Optional	
Loop: 0310	Elements: 3

User Option (Usage): Used

To transmit identifying information as specified by the Reference Identification Qualifier

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	<b>Reference Identification Qualifier</b>	M	ID	2/3	Must use
		<b>Description:</b> Code qualifying the Reference Identification				
		<b>Code Name</b>				
		PRT Product Type				
N902	127	<b>Reference Identification</b>	X	AN	1/50	Used
		<b>Description:</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier				
		<b>Dot Foods: IFDA Class Number</b>				
N903	369	<b>Free-form Description</b>	X	AN	1/45	Used
		<b>Description:</b> Free-form descriptive text				
		<b>Dot Foods: IFDA Class Description</b>				

## Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

## Semantics:

1. N906 reflects the time zone which the time reflects.
2. N907 contains data relating to the value cited in N902.

# UIT Unit Detail

Pos: 1520	Max: 10
Detail - Mandatory	
Loop: 0310	Elements: 1

User Option (Usage): Used

To specify item unit data

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
UIT01	C001	<b>Composite Unit of Measure</b>	M	Comp		Must use
		<b>Description:</b> To identify a composite unit of measure(See Figures Appendix for examples of use)				
	355	<b>Unit or Basis for Measurement Code</b>	M	ID	2/2	Must use
		<b>Description:</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				
		<b>Code Name</b>				
		BG Bag				
		CA Case				
		DR Drum				
		EA Each				
		GA Gallon				
		LB Pound				
		PA Pail				
		TE Tote				

## Syntax Rules:

1. C0302 - If UIT03 is present, then UIT02 is required.

## Dot Foods:

*Ordering Unit of Measure*

# MEA Measurements

Pos: 1530	Max: 10
Detail - Optional	
Loop: 0310	Elements: 4

User Option (Usage): Used

To specify physical measurements or counts, including dimensions, tolerances, variances, and weights(See Figures Appendix for example of use of C001)

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MEA01	737	<b>Measurement Reference ID Code</b>  <b>Description:</b> Code identifying the broad category to which a measurement applies  <b>Code Name</b> WT Weights	O	ID	2/2	Used
MEA02	738	<b>Measurement Qualifier</b>  <b>Description:</b> Code identifying a specific product or process characteristic to which a measurement applies  <b>Code Name</b> N Actual Net Weight	O	ID	1/3	Used
MEA03	739	<b>Measurement Value</b>  <b>Description:</b> The value of the measurement	X	R	1/20	Used
MEA04	C001	<b>Composite Unit of Measure</b>  <b>Description:</b> To identify a composite unit of measure(See Figures Appendix for examples of use)	X	Comp		Used
	355	<b>Unit or Basis for Measurement Code</b>  <b>Description:</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken  <b>Code Name</b> LB Pound	M	ID	2/2	Must use

## Syntax Rules:

1. R03050608 - At least one of MEA03, MEA05, MEA06 or MEA08 is required.
2. C0504 - If MEA05 is present, then MEA04 is required.
3. C0604 - If MEA06 is present, then MEA04 is required.
4. L07030506 - If MEA07 is present, then at least one of MEA03, MEA05 or MEA06 is required.
5. E0803 - Only one of MEA08 or MEA03 may be present.

## Semantics:

1. MEA04 defines the unit of measure for MEA03, MEA05, and MEA06.

**Comments:**

1. When citing dimensional tolerances, any measurement requiring a sign (+ or -), or any measurement where a positive (+) value cannot be assumed, use MEA05 as the negative (-) value and MEA06 as the positive (+) value.

# PAL Pallet Information

Pos: 1600	Max: >1
Detail - Optional	
Loop: 0311	Elements: 2

User Option (Usage): Used

To identify the type and physical attributes of the pallet, and, gross weight, gross volume, and height of the load and the pallet

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PAL03	885	<b>Pallet Blocks</b>	O	N0	1/3	Used
		<b>Description:</b> The number of pieces (cartons) per layer on the pallet				
PAL04	356	<b>Pack</b>	O	N0	1/6	Used
		<b>Description:</b> The number of inner containers, or number of eaches if there are no inner containers, per outer container				

## Syntax Rules:

1. P0506 - If either PAL05 or PAL06 is present, then the other is required.
2. C0710 - If PAL07 is present, then PAL10 is required.
3. C0810 - If PAL08 is present, then PAL10 is required.
4. C0910 - If PAL09 is present, then PAL10 is required.
5. L10070809 - If PAL10 is present, then at least one of PAL07, PAL08 or PAL09 is required.
6. P1112 - If either PAL11 or PAL12 is present, then the other is required.
7. P1314 - If either PAL13 or PAL14 is present, then the other is required.

## Semantics:

1. PAL04 (Pack) is the number of pieces on the pallet.
2. PAL05 (Unit Weight) is the weight of the pallet alone, before loading.
3. PAL07 and PAL08 (Length and Width) are the dimensions of the pallet before loading.
4. PAL09 (Height) is the height of the pallet and load.
5. PAL11 and PAL13 (Gross Weight and Gross Volume) are measured after loading and includes the pallet.

# G55 Item Characteristics - Consumer Unit

Pos: 1650	Max: 1
Detail - Optional	
Loop: 0312	Elements: 4

User Option (Usage): Used

To provide physical characteristics relative to a consumer unit

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
G5501	235	<b>Product/Service ID Qualifier</b>  <b>Description:</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)  <b>Code Name</b> UK EAN/UCC - 14	M	ID	2/2	Must use
G5502	234	<b>Product/Service ID</b>  <b>Description:</b> Identifying number for a product or service	M	AN	1/48	Must use
G5519	880	<b>Dated Product Number of Days</b>  <b>Description:</b> Used to designate the number of days open dated product must 'sell by' from date of manufacture  <b>Dot Foods: Shelf Life</b>	O	N0	1/4	Used
G5521	1073	<b>Yes/No Condition or Response Code</b>  <b>Description:</b> Code indicating a Yes or No condition or response  <b>Dot Foods: Hazardous Material</b>  <b>Code Name</b> N No Y Yes	O	ID	1/1	Used

## Syntax Rules:

1. P0304 - If either G5503 or G5504 is present, then the other is required.
2. P0506 - If either G5505 or G5506 is present, then the other is required.
3. P0708 - If either G5507 or G5508 is present, then the other is required.
4. P0910 - If either G5509 or G5510 is present, then the other is required.
5. P1112 - If either G5511 or G5512 is present, then the other is required.
6. P1415 - If either G5514 or G5515 is present, then the other is required.
7. P232425 - If either G5523, G5524 or G5525 are present, then the others are required.
8. P262728 - If either G5526, G5527 or G5528 are present, then the others are required.
9. P2930 - If either G5529 or G5530 is present, then the other is required.

## Semantics:

1. G5521 indicates if the product is prepriced. Code "Y" indicates the product is prepriced. Code "N" indicates the product is not

prepriced.

**Comments:**

1. G5516 is limited to 16 characters.

# REF Reference Identification

Pos: 1775	Max: 10
Detail - Optional	
Loop: 0312	Elements: 3

User Option (Usage): Used

To specify identifying information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	<b>Reference Identification Qualifier</b> <b>Description:</b> Code qualifying the Reference Identification <b>Code Name</b> PHC Process Handling Code	M	ID	2/3	Must use
REF02	127	<b>Reference Identification</b> <b>Description:</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier <b>Dot Foods: Crushability Code</b>	X	AN	1/50	Used
REF03	352	<b>Description</b> <b>Description:</b> A free-form description to clarify the related data elements and their content <b>Dot Foods: Crushability Description</b>	X	AN	1/80	Used

## Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

## Semantics:

1. REF04 contains data relating to the value cited in REF02.

# SE Transaction Set Trailer

Pos: 2000	Max: 1
Detail - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	<b>Number of Included Segments</b>	M	N0	1/10	Must use
		<b>Description:</b> Total number of segments included in a transaction set including ST and SE segments				
SE02	329	<b>Transaction Set Control Number</b>	M	AN	4/9	Must use
		<b>Description:</b> Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

## Comments:

1. SE is the last segment of each transaction set.

# GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

To indicate the end of a functional group and to provide control information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	<b>Number of Transaction Sets Included</b>	M	N0	1/6	Must use
		<b>Description:</b> Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element				
GE02	28	<b>Group Control Number</b>	M	N0	1/9	Must use
		<b>Description:</b> Assigned number originated and maintained by the sender				

## Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

## Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

# IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To define the end of an interchange of zero or more functional groups and interchange-related control segments

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	<b>Number of Included Functional Groups</b> <b>Description:</b> A count of the number of functional groups included in an interchange	M	N0	1/5	Must use
IEA02	I12	<b>Interchange Control Number</b> <b>Description:</b> A control number assigned by the interchange sender	M	N0	9/9	Must use

# Table of Contents

<b>888</b>	<b>Item Maintenance</b> .....	<b>2</b>
	<b>ISA Interchange Control Header</b> .....	<b>4</b>
	<b>GS Functional Group Header</b> .....	<b>7</b>
	<b>ST Transaction Set Header</b> .....	<b>9</b>
	<b>N1 Name</b> .....	<b>10</b>
	<b>N3 Address Information</b> .....	<b>11</b>
	<b>N4 Geographic Location</b> .....	<b>12</b>
	<b>N1 Name</b> .....	<b>13</b>
	<b>N3 Address Information</b> .....	<b>14</b>
	<b>N4 Geographic Location</b> .....	<b>15</b>
	<b>G61 Contact</b> .....	<b>16</b>
	<b>G61 Contact</b> .....	<b>17</b>
	<b>G62 Date/Time</b> .....	<b>18</b>
	<b>G53 Maintenance Type</b> .....	<b>19</b>
	<b>NTE Note/Special Instruction</b> .....	<b>20</b>
	<b>LX Assigned Number</b> .....	<b>21</b>
	<b>G39 Item Characteristics - Vendor's Selling Unit</b> .....	<b>22</b>
	<b>G69 Line Item Detail - Description</b> .....	<b>26</b>
	<b>G69 Line Item Detail - Description</b> .....	<b>27</b>
	<b>G69 Line Item Detail - Description</b> .....	<b>28</b>
	<b>G69 Line Item Detail - Description</b> .....	<b>29</b>
	<b>LIN Item Identification</b> .....	<b>30</b>
	<b>G23 Terms of Sale</b> .....	<b>32</b>
	<b>G26 Pricing Conditions</b> .....	<b>34</b>
	<b>N9 Reference Identification</b> .....	<b>35</b>
	<b>N9 Reference Identification</b> .....	<b>36</b>
	<b>N9 Reference Identification</b> .....	<b>37</b>
	<b>UIT Unit Detail</b> .....	<b>38</b>
	<b>MEA Measurements</b> .....	<b>39</b>
	<b>PAL Pallet Information</b> .....	<b>41</b>
	<b>G55 Item Characteristics - Consumer Unit</b> .....	<b>42</b>
	<b>REF Reference Identification</b> .....	<b>44</b>
	<b>SE Transaction Set Trailer</b> .....	<b>45</b>
	<b>GE Functional Group Trailer</b> .....	<b>46</b>
	<b>IEA Interchange Control Trailer</b> .....	<b>47</b>